

ACE

VEER 3000 4WD

ACE INDIA'S NO. 1
CRANE BRAND



Power : 26 HP
Drive : 4WD



Standard Features 4WD
Engine

Make	MITSUBISHI
Model	MVS3L2
Emission	Stage 5
HP / kW	26 / 18.2
No. of Cylinders	3
Bore/Stroke (mm)	78/92
Cubic Capacity (cc)	1318
Rated RPM	2500 ± 30
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Max Torque (Nm @ RPM)	76.3@2000
Exhaust	Underhood Downdraft

Transmission

Drive	4WD
Clutch	Single Clutch
Gearbox	6F + 2R
Transmission Type	Sliding Mesh

PTO

Independent PTO	540 / 540 E
PTO (actuation)	Mechanically actuated, Hand operated

Electrical

Battery (V, Ah)	12, 65
Alternator (V, A)	12, 65
Trailer Socket	Yes, Seven Pin (Round)

DCV

DCV	Yes
-----	-----

Standard Features 4WD
Steering

Steering	Power
----------	-------

Speed Forward

Min Speed (Km/h) @ rpm	1.32@2500
Max Speed (Km/h) @ rpm	14.73@2500

Brakes

Brakes	Oil Immersed Disc Brakes
Type of Actuation	Mechanically actuated
Hand Brake	Yes, Hand Operated

Safety Switches

PTO	Yes
Clutch Safety	Yes
Neutral Safety	Yes
Parking Safety	Yes

Hydraulics

3 Point Linkage	CAT1N
Auxiliary Hydraulic Circuit	1DA
Hydraulic Lifting Capacity (kg) hitch point	800

Others

Mechanical Coupling	Swinging Drawbar
Driver Seat	Horizontally adjustable
Fuel Indicator Gauge	Yes
Front Tow Hook	Yes
ROPS	Yes

Standard Features 4WD
Weight

Front Weight	Front weight carrier (hanging weight optional)
--------------	---

Capacity (L)

Fuel Tank	25
Power Steering System	1.8
Engine Oil	4
Hydraulic+Transmission	17
Front Axle	2.5

Dimension & Weight

Weight (kg)	1040
Wheel Base (mm)	1365
Total Length (mm)	2800
Total Width (mm)	1170
Height (mm)	2500
Ground Clearance (mm)	227
Front Track, (mm)	940
Rear Track, (mm)	870

Tyres

Industrial Tyre (Front, Rear)	23x8.50-12 & 33x15.5-16.5
Turf Tyre (Front, Rear)	23x8.50-12 & 33x15.5-16.5
Radial Tyres	6.5/80-12 & 280/70R20
Agri Tyre (Standard)	6.00-12 & 8.3x20

